



Commercial[®] 95 340

Architectural Shade Fabric

TENSION STRUCTURES

AWNINGS

SHADE SAILS



GALE
P A C I F I C


Commercial[®] 95 340

Architectural Shade Fabric



Gale Pacific's Commercial 95[®] 340 Architectural Shade Fabrics is designed for tension structures and shade sails, it is used on a wide variety of applications. It offers the ultimate combination of **maximum sun protection, strength and durability** to ensure maintenance-free long-life performance.

Engineered in Australia, Commercial 95[®] 340 is made from high-quality UV-stabilised HDPE. Strong and stable, it's suitable for harsh Australian conditions. It's 100% lead and phthalate-free, and we're proud to state it is the first architectural shade cloth in the world to be granted Oeko-Tex[®] 100 and Greenguard[®] certification.



- Knitted lock-stitch construction for fray and tear resistance, offers more air movement and better channeling of cool breezes
- UV-stabilised HDPE monofilament and tape yarn provides optimal balance between strength and UV block, with easy fabrication and minimal maintenance
- Stentered (heat set) for prevention of shrinking and ease of fabrication
- UV Block range 90.6%–96.2% reduces sun exposure for safe and extended time outdoors
- Full 10-year UV degradation warranty on fabric
- 100% lead and phthalate free for a healthier environment
- Greenguard[®] and Oeko-Tex[®] certified provides confidence in operational quality assurance
- Engineered in Australia for the harshest conditions
- 100% recyclable

Properties

Nominal fabric mass	340gsm ± 20
Roll length (m)	40 (folded) 100 (unfolded)
Roll width (m)	3


Performance

Maximum force - warp (mean)	670 N/50mm
Elongation at max. force (mean)	117%
Maximum force - weft (mean)	2400 N/50mm
Elongation at max. force (mean)	83%
Breaking force - warp (mean)	990 N
Breaking force - weft (mean)	2000 N
Wing tear - warp (mean)	184 N
Wing tear - weft (mean)	347 N
Bursting pressure (mean)	3500 kPa
Bursting force (mean)	1937 N
Flammability index	12


Applications

- Tension structures
- Awnings
- Shade sails
- Car Park structures






Natural 445003 | 483951
95.2% UVR Block




Aquatic Blue 444938 | 483937
91.8% UVR Block




Black 444945
95.5% UVR Block




Navy Blue 445010
93.2% UVR Block



Sky Blue 445034
95.2% UVR Block




Brunswick Green 444952 | 483975
94.4% UVR Block



Cayenne 455255
92.7% UVR Block




Cedar 465360
94.1% UVR Block




Charcoal 444969
94.7% UVR Block



Cherry Red 444976
90.6% UVR Block




Desert Sand 444983 | 483845
93.7% UVR Block




Gun Metal 455262 | 483944
91.8% UVR Block




Yellow 445072
94.5% UVR Block




Deep Ochre 444990
94.8% UVR Block




River Gum Green 445027
93.4% UVR Block




Steel Grey 445041 | 483968
94.8% UVR Block



Turquoise 445065
93.4% UVR Block



Royal Purple 459185
93.6% UVR Block



Bright Green 459215
96.2% UVR Block



Orange 459208
94.6% UVR Block



galecommercial.com

AU P 1800 331 521

NZ P 0800 555 171

UAE P +971 4 881 7114

USA P 1800 560 4667