



Commercial[®] 95 340

Architectural Shade Fabric

TENSION STRUCTURES

AWNINGS

SHADE SAILS

GALE
PACIFIC

galecommercial.com

AU P 1800 331 521

NZ P 0800 555 171

UAE P +971 4 881 7114

USA P 1800 560 4667

GALE
PACIFIC



Commercial[®] 95 340

Architectural Shade Fabric



Gale Pacific's Commercial 95[®] 340 Architectural Shade Fabrics is designed for tension structures and shade sails, it is used on a wide variety of applications. It offers the ultimate combination of **maximum sun protection, strength and durability** to ensure maintenance-free long-life performance.

Engineered in Australia, Commercial 95[®] 340 is made from high-quality UV-stabilised HDPE. Strong and stable, it's suitable for harsh Australian conditions. It's 100% lead and phthalate-free, and we're proud to state it is the first architectural shade cloth in the world to be granted Oeko-Tex[®] 100 and Greenguard[®] certification.



- Knitted lock-stitch construction for fray and tear resistance, offers more air movement and better channeling of cool breezes
- UV-stabilised HDPE monofilament and tape yarn provides optimal balance between strength and UV block, with easy fabrication and minimal maintenance
- Stentered (heat set) for prevention of shrinking and ease of fabrication
- UV Block range 89.3%–97.7% reduces sun exposure for safe and extended time outdoors
- Full 10-year UV degradation warranty on fabric
- 100% lead and phthalate free for a healthier environment
- Greenguard[®] and Oeko-Tex[®] certified provides confidence in operational quality assurance
- Engineered in Australia for the harshest conditions
- 100% recyclable

Properties


Nominal fabric mass	340gsm ± 20
Roll length (m)	40 (folded) 100 (unfolded)
Roll width (m)	3

Performance


Tensile strength - warp	635N / 50mm
Elongation at break (%)	95.6
Tensile strength - weft	2494N / 50mm
Elongation at break (%)	70.4
Wing tear - warp (mean)	187N
Wing tear - weft (mean)	359N
Bursting pressure (mean)	3500 kPa
Bursting force (mean)	2146N
Flammability index	14

Applications

- Tension structures
- Awnings
- Shade sails
- Car Park structures




Natural 445003 | 483951
96.8% UVR Block




Aquatic Blue 444938 | 483937
93.6% UVR Block




Black 444945
97.4% UVR Block




Navy Blue 445010
95.2% UVR Block




Sky Blue 445034
93.8% UVR Block




Brunswick Green 444952 | 483975
95.1% UVR Block




Cayenne 455255
94.0% UVR Block




Cedar 465360
94.7% UVR Block



Charcoal 444969
94.7% UVR Block




Cherry Red 444976
89.3% UVR Block




Desert Sand 444983 | 483845
96.4% UVR Block




Gun Metal 455262 | 483944
97.7% UVR Block




Yellow 445072
97.1% UVR Block




Deep Ochre 444990
94.4% UVR Block



River Gum Green 445027
92.3% UVR Block



Steel Grey 445041 | 483968
93.0% UVR Block



Turquoise 445065
94.3% UVR Block

^ Available in made to order only, contact your GALE Pacific representative for lead time information
Please note, due to the limitations of the printing process, colours may not represent the true colour