

# Hailguard™



Material Safety Data Sheet

Commercial Knitted

Page 1 of 2  
Rev.2 09/06

## Identification

<b>Product Name</b>	Hailguard™	<b>UN Number</b>	Not Applicable
<b>Other Names</b>	Hailguard™	<b>Hazchem Code</b>	Not Applicable
<b>Product Code</b>	Refer to respective Product Profile	<b>Dangerous Goods Class</b>	Not Applicable
		<b>Poisons Schedule</b>	Not Applicable
<b>Application</b>	General purpose netting for bird and pest control		

## Physical Description & Properties

<b>Appearance</b>	Odourless knitted fabric in white and black	<b>Flashpoint</b>	Not applicable
<b>Melting point</b>	Approx. 140°C (284°F)	<b>Flammability limits</b>	
<b>Vapour pressure</b>	Not applicable	<b>Solubility in water</b>	Insoluble
<b>Specific Gravity</b>	Approx 0.9		
<b>Other properties</b>			
<b>Ingredients</b>			

Chemical Entity	CAS no.	Proportion
Polyethylene	2002-88-4	~ 95%
Other proprietary pigments and additives	-	~ 4%
Hindered amine light stabiliser	-	~ 1%

## Health Effects

### Exposure

<b>Ingestion</b>	This product is of a solid nature and should not be swallowed.	<b>First Aid</b>	If necessary, seek medical advice.
<b>Eye</b>	May irritate the eye from physical contact.	<b>First Aid</b>	This product is of a solid nature and should not contact the eye. Seek medical advice.
<b>Skin</b>	This fabric may be fabricated using high temperature equipment - beware of molten material.	<b>First Aid</b>	If molten plastic contacts the skin, cool affected area rapidly under cold, clean running water. Do not peel molten plastic from skin. Seek medical advice.
<b>Inhalation</b>	Avoid fumes and or dust generated from, welding, burning or dust from other handling	<b>First Aid</b>	If affected by fumes or dust, remove to a clean well ventilated area. If necessary, seek medical advice

The above results are typical averages from quality assurance testing and are not to be taken as a minimum specification nor as forming any contract between GALE Pacific and another party. Due to continuous product improvement product specifications are subject to alteration without notice.

As the use and disposal of this product are beyond GALE Pacific's control, regardless of any assistance provided without charge, GALE Pacific assumes no obligation or liability for the suitability of its products in any specific end use application. It is the customer's responsibility to determine whether GALE Pacific's products are appropriate for the specific application and complies with any legal & patent regulations.

<b>AU</b>	P 1800 331 521	F +61 3 9518 3398	gpcommercial.com
<b>NZ</b>	P 0800 555 171	F 0800 555 172	
<b>UAE</b>	P +971 4 881 7114	F +971 4 881 7167	
<b>USA</b>	P 1800 560 4667	F +1 407 772 0553	gpcommercialusa.com

## Precautions For Use

<b>Exposure standards</b>	Not established
<b>Engineering controls</b>	Fabricate in normal well ventilated areas, use additional ventilation or exhaust extraction systems when welding or hot knife cutting.
<b>Personal protection</b>	Use of general purpose protective gloves is recommended (but not essential) when handling fabric. Wash hands after working with fabric.
<b>Flammability</b>	Combustible but of low flammability. Extinguish by using water spray or extinguisher foam.
<b>Environment</b>	Not hazardous to water. May not break down readily when exposed to microbial attack during landfill disposal.

## Storage Requirements

<b>Storage</b>	Store in a cool dry area away from direct sunlight, halogens and highly acidic substances.
<b>Handling &amp; transport</b>	Use caution when loading and unloading fabric from vehicles. Refer to Product Profile for approximate roll weights.
<b>Spills &amp; Disposal</b>	The product is solid and therefore not subject to spillage. Incinerate under controlled conditions according to local regulations or dispose as an inert solid in a land fill according to local regulations. This product may be recycled – contact your local authorities.
<b>Fire &amp; Explosion</b>	The product may accumulate static charges which may cause an incendiary electrical discharge. Thermal decomposition temperature is approximately 280-300°C (536-572°F) combustion may produce ash particulates, with gases including carbon dioxide, carbon monoxide, oxides of nitrogen and sulphur as well as extremely small quantities of other organic chemicals including acrolein.

## OTHER INFORMATION

The resins and additives used in the material are not suitable for food contact.

## CONTACT POINT

Marketing Manager – Commercial Fabrics  
Telephone: (03) 9518 3333

*The above results are typical averages from quality assurance testing and are not to be taken as a minimum specification nor as forming any contract between GALE Pacific and another party. Due to continuous product improvement product specifications are subject to alteration without notice.*

*As the use and disposal of this product are beyond GALE Pacific's control, regardless of any assistance provided without charge, GALE Pacific assumes no obligation or liability for the suitability of its products in any specific end use application. It is the customer's responsibility to determine whether GALE Pacific's products are appropriate for the specific application and complies with any legal & patent regulations.*